

Underceiling & Floor Standing

Cooling & Heating



Features



Waterproof



Auto Swing & Wide
angle airflow



Auto-restart



24 hr timing



Auto defrost



Easy-washable and
easy-moveable filter



Elegant design



A U C 3 6
A U C 4 8
A U C 6 0

Technical Data

Model		AUC 36	AUC 48	AUC 60
Function		Cooling/Heating	Cooling/Heating	Cooling/Heating
Capacity	W	10 500/11 400	14 070/15 535	17 585/19 930
	BTU	36 000/39 000	48 000/53 000	60 000/68 000
Electrical Data				
Voltage/Frequency/Phase	V, Hz, Ph	380, 50, 3	380, 50, 3	380, 50, 3
Running Current	Cooling	A	6.5	8.2
	Heating	A	5.8	8.6
Starting Current	A	59	59	67
Air Flow Volume	(m ³ /h)	1 600/1 200/1 000	2 000/1 800/1 600	2 200/1 800/ 1 600
Noise Levels	dB(A)	45/43/40	47/46/40	47/46/44
Max pipe run	m	25	25	30
Max difference in (v)	m	10	10	15
Refrigerant piping				
Liquid line/gas line	inch	0,5/0,75	0,5/0,75	0,5/0,75
Net Weight in/out	(Kg)	35/112	52/114	52/114
Gross Weight in/out	(Kg)	40/127	59/127	62/135
Dimensions net In Unit				
Dimensions net Out Unit	WxHxD(mm)	1 285 x 660 x 198	1 670 x 680 x 240	1 670 x 680 x 240
Dimension In Packaged	WxHxD(mm)	1 379 x 744 x 296	1 764 x 760 x 330	1 764 x 760 x 330
Dimension Out Packaged	WxHxD(mm)	1 120 x 1 090 x 435	1 120 x 1 090 x 435	1 058 x 1 370 x 435
Gas		R22	R22	R22

* The data is subject to
modification without notice.



**Sold, distributed and
nationally supported:**

Gauteng & Central Region
0860 726 247

Western, Eastern &
Northern Cape
(021) 556-8292

Kwa-Zulu Natal
(031) 579-1895

AllianceAir

AllianceAir

a i r c o n d i t i o n e r s

Distributed by: Fourways Airconditioning - 011 704 6320 ■ Clorpique - 031 579 1895 ■ SamAir - 021 556 8292

AllianceAir

AllianceAir