



GLASS DOOR

JUST FOR QUALITY, JUST FOR PRICE, JUST FOR YOU



GD4S/C



GD6SL/D



GD8S/C

FEATURES

Stainless steel grade 430 satin finish no 4 for sides, top and front grid
 Galvanised steel – rear and bottom
 Polyurethane foam injected insulation
 Robust top & bottom hinges
 Fully adjustable heavy duty plastic coated shelves
 Digital temperature display with hi/low voltage protection
 Self-closing doors
 Robust handles on doors
 All underbars supplied with brake castors.
 Dual thermopane safety glass used for glass doors
 Adjustable thermostat 2 to 6 degrees Celsius.
 Auto evaporation (The condensate is evaporated hence no need to drain)
 All models are 220v – Plug in and switch on
 Interior lighting with switch
 Heavy duty sliding rail on sliding door models

OPTIONAL EXTRAS

Adjustable levelling feet • Combination of glass and steel doors • 650 deep • 850 height • Splash backs – rear or left and right hand ends • Locks / locking bar • Blue lights • Additional shelving • Heated glass doors (requires heated mullions) • Right hand side compressor • 304 stainless steel • Cutting board • Inserts and lids • GN1 & SK5 Tray slides • Speed rails • Glass on both sides • Stainless steel backing • All units available in remote – with exception of the sliding door models

SWING DOOR		GD4S/C	GD6S/C	GD8S/C
Doors		1.5	2.5	3.5
Height (with castors)	mm	900	900	900
Width	mm	1180	1780	2380
Depth	mm	650/750	650/750	650/750
Working Temperature	°C	+2 - +6	+2 - +6	+2 - +6
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	319	580	840

SLIDING DOOR		GD6SL/D	GD8SL/D
Doors		2	4
Height (with castors)	mm	900	900
Width	mm	1780	2380
Depth	mm	750	750
Working Temperature	°C	+2 - +6	+2 - +6
Refrigerant		R134A	R134A
Internal Volume	litres	607	877

AVAILABLE IN REMOTE AND SELF CONTAINED



STAINLESS STEEL DOOR

JUST FOR QUALITY, JUST FOR PRICE, JUST FOR YOU



QUB6S/C

* CASTORS AS STANDARD LEGS ARE OPTIONAL

FEATURES

- Stainless steel grade 430 satin finish no 4 for sides, top and front grid
- Galvanised steel – rear and bottom
- Polyurethane foam injected insulation
- Robust top & bottom hinges
- Fully adjustable heavy duty plastic coated shelves
- Digital temperature display with hi/low voltage protection
- Self-closing doors
- Robust handles on doors
- All underbars supplied with brake castors.
- Adjustable thermostat 2 to 6 degrees Celsius.
- Auto evaporation (The condensate is evaporated hence no need to drain)
- All models are 220v – Plug in and switch on

	SOLID DOORS	QUB4S/C	QUB6S/C	QUB8S/C
Door		1.5	2.5	3.5
Height (with castors)	mm	900	900	900
Width	mm	1180	1780	2380
Depth	mm	650/750	650/750	650/750
Working Temperature	°C	+2 - +6	+2 - +6	+2 - +6
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	319	580	840

ALSO AVAILABLE IN REMOTE

OPTIONAL EXTRAS

- Adjustable levelling feet
- Combination of glass and steel doors
- 650 deep
- 850 height
- Splash backs – rear or left and right hand ends
- Locks / locking bar
- Additional shelving
- Right hand side compressor
- 304 stainless steel
- Cutting board
- GN1 & SK5 Tray slides
- Drawers
- Speed rails
- Stainless steel backing
- All units available in remote



POLAR TOP

JUST FOR QUALITY, JUST FOR PRICE, JUST FOR YOU



QUB6PLTS/C

* CASTORS AS STANDARD LEGS ARE OPTIONAL

FEATURES

Stainless steel grade 430 satin finish no 4 for sides, top and front grid
Galvanised steel – rear and bottom
Polyurethane foam injected insulation
Robust top & bottom hinges
Fully adjustable heavy duty plastic coated shelves
Digital temperature display with hi/low voltage protection
Self-closing doors
Robust handles on doors
All underbars supplied with brake castors.
Adjustable thermostat 2 to 6 degrees Celsius.
Auto evaporation (The condensate is evaporated hence no need to drain)
All models are 220v – Plug in and switch on

SWING DOORS		QUB4PLT S/C	QUB6PLT S/C	QUB8PLT S/C
Door		1.5	2.5	3.5
Height	mm	900	900	900
Width	mm	1180	1780	2380
Depth	mm	650/750	650/750	650/750
Working Temperature	°C	+2 - +6	+2 - +6	+2 - +6
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	200	450	700

OPTIONAL EXTRAS

Adjustable levelling feet • Combination of glass and steel doors • 650 deep • 850 height • Splash backs – rear or left and right hand ends • Locks / locking bar • Additional shelving • Right hand side compressor • 304 stainless steel • Cutting board • GN1 & SK5 Tray slides • Drawers • Speed rails • Stainless steel backing • All units available in remote •



GASTRANORM

JUST FOR QUALITY, JUST FOR PRICE, JUST FOR YOU



GD3G

* CASTORS AS STANDARD LEGS ARE OPTIONAL

* INSERTS NOT INCLUDED

FEATURES

Stainless steel grade 430 satin finish no 4 for sides, top and front grid
Galvanised steel – rear and bottom
Polyurethane foam injected insulation
Robust top & bottom hinges
Fully adjustable heavy duty plastic coated shelves
Digital temperature display with hi/low voltage protection
Self-closing doors
Robust handles on doors
All underbars supplied with brake castors.
Dual thermopane safety glass used for glass doors
Adjustable thermostat 2 to 6 degrees Celsius.
Auto evaporation (The condensate is evaporated hence no need to drain)
All models are 220v – Plug in and switch on

OPTIONAL EXTRAS

Adjustable levelling feet • Combination of glass and steel doors • 650 deep • 850 height • Splash backs – rear or left and right hand ends • Locks / locking bar • Additional shelving • Right hand side compressor • 304 stainless steel • Cutting board • GN1 & SK5 Tray slides • Drawers • Speed rails • Stainless steel backing • All units available in remote •

	SOLID DOORS	QUB2G	QUB3G	QUB4G
Door		2	3	4
Height	mm	900	900	900
Width	mm	1335	1780	2380
Depth	mm	650/750	650/750	650/750
Working Temperature	°C	+2 to +6	+2 to +6	+2 to +6
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	310	500	700

	GLASS DOOR	GD2G	GD3G	GD4G
Door		2	3	4
Height	mm	900	900	900
Width	mm	1335	1780	2380
Depth	mm	750	750	750
Working Temperature	°C	+2 to +6	+2 to +6	+2 to +6
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	310	500	700



ROLL TOP

JUST FOR QUALITY, JUST FOR PRICE, JUST FOR YOU



QUB6RTS/C

FEATURES

- Stainless steel grade 430 satin finish no 4 for sides, top and doors
- Galvanised steel – rear and bottom
- Polyurethane foam injected insulation
- Fully adjustable heavy duty plastic coated shelves
- Digital temperature display with hi/low voltage protection
- Self-closing doors
- Recessed handles on solid doors
- All underbars supplied with brake castors.
- Adjustable thermostat 2 to 6 degrees Celsius.
- Auto evaporation (The condensate is evaporated hence no need to drain)
- All models are 220v – Plug in and switch on
- Bottom Loading Doors
- Depth change as option

		QUB4RT S/C	QUB6RT S/C	QUB8RT S/C
Doors		1	2	3
Roll Tops		2	3	4
Height (with castors)	mm	900	900	900
Width	mm	1180	1780	2380
Depth	mm	750	750	750
Working Temperature	°C	+2 - +6	+2 - +6	+2 - +6
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	300	510	720

OPTIONAL EXTRAS

- Adjustable levelling feet • Locks/locking bar • Additional shelving • Right hand side compressor • 304 stainless steel • Speed rails • Stainless steel backing •



PIZZA TOP

JUST FOR QUALITY, JUST FOR PRICE, JUST FOR YOU



QUB6PZTS/C

* CASTORS AS STANDARD LEGS ARE OPTIONAL

FEATURES

Stainless steel grade 430 satin finish no 4 for sides, top and front grid
Galvanised steel – rear and bottom
Polyurethane foam injected insulation
Robust top & bottom hinges
Fully adjustable heavy duty plastic coated shelves
Digital temperature display with hi/low voltage protection
Self-closing doors
Robust handles on doors
All underbars supplied with brake castors.
Dual thermopane safety glass used for glass doors
Adjustable thermostat 2 to 6 degrees Celsius.
Auto evaporation (The condensate is evaporated hence no need to drain)
All models are 220v – Plug in and switch on

OPTIONAL EXTRAS

Adjustable levelling feet • Combination of glass and steel doors • 650 deep • 850 height • Splash backs – rear or left and right hand ends • Locks / locking bar • Additional shelving • Right hand side compressor • 304 stainless steel • Cutting board • GN1 & SK5 Tray slides • Drawers • Speed rails • Stainless steel backing • All units available in remote •

		GD4PZT S/C QUB4PZT S/C	GD6PZT S/C QUB6PZT S/C	GD8PZT S/C QUB8PZT S/C
Door		1.5	2.5	3.5
Height (with castors)	mm	900	900	900
Width	mm	1180	1780	2380
Depth	mm	650/750	650/750	650/750
Working Temperature	°C	+2°C - +6°C	+2°C - +6°C	+2°C - +6°C
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	319	580	750

		QUB2GPZT GD2GPZT	QUB3GPZT GD3GPZT	QUB8GPZT GD4GPZT
Door		2	3	4
Height (with castors)	mm	900	900	900
Width	mm	1335	1780	2380
Depth	mm	650/750	650/750	650/750
Working Temperature	°C	+2 - +6	+2 - +6	+2 - +6
Refrigerant		R134A	R134A	R134A
Internal Volume	litres	310	500	700