



STARWAY

Starway Wall Split Series



24-hour Programmable
Timer



Anti-Cold Air Function



Auto 3 Stage Fan Speed



Emergency Operation



Dry Mode



Removable Front
Panel for Easy Cleaning



Sleep Mode



Air Swing



High Power Running



Long Piping Lengths
For Installation Flexibility



Super Quiet Operation



Auto Defrost



Air-Purifying Filter

Model	Model	*Starway 9000E	Starway9000	*Starway 12000E	Starway 12000	Starway 18000	Starway 24000
	Code	KFR-25GWVK	KFR-25GWVJ	KFR-32GWVK	KFR-32GWVJ	KFR-50GWVJ	KFR-70GWVJ
Cooling Capacity	W	2500	2500	3200	3200	4850	6500
Heating Capacity	W	2750	2750	3520	3520	5500	7700
Power Supply	VHz	1PH, 220V, 50Hz	1PH, 220V, 50Hz	1PH, 220V, 50Hz	1PH, 220V, 50Hz	1PH, 220V, 50Hz	1PH, 220V, 50Hz
Rated Cooling power input	W	930	930	1200	1200	1900	2426
Rated Cooling current input	A	4.3	4.3	5.5	5.5	8.7	11.2
Rated Heating power input	W	890	890	1150	1150	1860	2712
Rated Heating current input	A	4.2	4.2	5.3	5.3	8.6	12.6
Noise Level	dB(A)	37	37	37	37	46	51
Air Flow (Inside)	M ³ /h	435	435	500	500	860	880
Dimensions (L x W x H) mm	Inside	677X198X250	677X198X250	745X198X250	745X198X250	900X211X285	1014X213X320
	Outside	650X250X506	650X250X506	760X259X537	760X259X537	760X259X537	950X310X712
Net Weight (kg)	Inside	9.5	9.5	10	10	13	17.5
	Outside	29.5	29.5	35	35	45	71
Supplied Copper Pipe (Imperial Connections)	Metres	3.0	3.0	3.4	3.4	4.0	4.0

* Economy Model - No LED Display on Inside Unit

Available from: